



www.clarkemfg.com

503-829-2156

Clarke Manufacturing Inc. 13388 S. Molalla Forest Rd. Molalla OR. 97038

Toll free 1-800-232-2002 Fax 503-829-6269 E-mail Sales@clarkemfg.com



READ FIRST TANK INSTALLATION READ FIRST

Install fuel tank **ONLY** in a well ventilated area. Clean inside of tank thoroughly before installation. **DO NOT** start or operate the vehicle if there are any fuel leaks. We recommend that installation be performed by a qualified mechanic. If you have any questions **CALL FIRST**, before attempting to install.

This is an optional Fuel petcock for the following Clarke Fuel Tanks.

11409 - DRZ 400S (00-13) & KLX 400SR (03-05) Dual Sport 3.9gal

11479 - DRZ 400E (00-08) & KLX 400R (03-05) 3.6gal

1. Fuel petcock
2. Clarke Rubber Grommet
3. 3/16 Rubber Cap

First, drain the fuel from your tank. Next, remove the tank from the bike. Then take off the old fuel valve. Where the canister line comes into the Fuel petcock you will block off with the 3/16 cap provided. Place the rubber gasket provided directly onto your Tank. Using the screws provided attach the fuel valve to the bottom of the tank. Now, remove the fuel line from the old fuel valve and place it on the new fuel valve. Cut the fuel line to the appropriate length. Attach the fuel line to the hard line that feeds into the engine. Now turn on the fuel. Enjoy your ride!